



Product Catalog - Touring High Tech Diesel Specialoil 15 W-40

Products



Touring High Tech Diesel Specialoil 15 W-40

- universal use for petrol and diesel engines with and without exhaust-gas turbocharging and with and without charge air cooling
- good cold-start behaviour
- high lubricating film stability and high wear protection
- low evaporation losses
- high shear and ageing stability
- good cleanliness and dispersant properties
- prevents black sludge
- miscible with all commercially available engine oils
- tested for catalytic converter compatibility
- neutralises negative effects from fuels

article number: 2044

bundle content: 5 l

palette content: 112

packing unit: 4 STK

language: GB - F - E - USA - CAN

Intended use

Year-round engine oil for aspirated and turbocharged Diesel engines. Especially suitable for extreme running conditions.

Clearing

ACEA B2-98/E2-96 ; API CF-4 ; Allison C-4 ; Caterpillar TO-2 ; Mack EO-K2 ; MB-Freigabe 228.1 ; MIL-L 46152 E ; ZF TE-ML 04 C/ 07 C

LIQUI MOLY advise this product for vehicles with the following specifications: MTU Typ 2 ; VW 501.01 / 505.00

Kontakt Daten:

LIQUI MOLY GMBH
Jerg-Wieland-Strasse 4
D-89081 Ulm-Lehr

phone: 0731-1420-0
fax: 0731-1420-71
e-mail: info@liqui-moly.de
internet: www.liqui-moly.de

source: http://www.liqui-moly.com/liquimoly/produktdb.nsf/id/usa_2044.html