

1 / 5 EN

Revision: 17.07.2003 Replaces the version of: 17.07.2003 Printing date: 05.02.2004

VOLLSYNT.ENERGY MOT.OIL0W40 5L

Art.:2050

## Safety Data Sheet according to EEC-Regulation 91/155/EEC

### 1. Identification of the substance/preparation and of the company/undertaking

#### Identification of the substance or preparation

**VOLLSYNT.ENERGY MOT.OIL0W40 5L**

**Art.:2050**

#### Use of the substance/preparation

Refer to description of material or preparation.

#### Company/undertaking identification

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081, Ulm-Lehr  
Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

#### Emergency telephone / Office for advice

##### Advisory office in case of poisoning:

Tel.:

##### Telephone number of the company in case of emergencies:

Tel. (+49) 0731-1420-0

### 2. Composition/information on ingredients

2.1 Chemical name	content %	symbol	R-phrases	CAS	EINECS, ELINCS
Zinc alkyl dithiophosphate	1 -< 2,5	Xi/N	38-41-51-53		272-028-3
For complete wording of the R-phrases, refer to point 16.					

### 3. Hazards identification

#### 3.1 To people

See point 11 and 15.

Preparation is not classified as hazardous in the sense of directive 1999/45/EG.

#### 3.2 To the environment

See point 12.

Product can compose a film on the water surface, which can prevent oxygen exchange.

### 4. First aid measures

#### 4.1 Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Remove person from danger area.

#### 4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

#### 4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### 4.4 Ingestion

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

#### 4.5 Special resources necessary for first aid

n.g.

### 5. Fire-fighting measures

### 5.1 Suitable extinguishing media

CO2  
Foam  
Water jet spray

### 5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

### 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Oxides of sulphur  
Flammable vapour/air mixtures.

### 5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply  
According to size of fire  
Full protection, if necessary

### 5.5 Further information

Dispose of contaminated extinction water according to official regulations.

## 6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

### 6.1 Personal precautions

Avoid inhalation, and contact with eyes or skin.  
Caution - risk of slipping.  
Do not carry cleaning cloths soaked in product in trouser pockets.

### 6.2 Environmental measures

If leakage occurs, dam up.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

## 7. Handling and storage

### 7.1 Handling

#### Tips for safe handling:

See point 6.1  
Ensure good ventilation.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Wash hands before breaks and at end of work.  
General hygiene measures for the handling of chemicals are applicable.  
Take measures against electrostatic charging, if appropriate.  
Observe directions on label and instructions for use.  
Recommended  
Exposed employees should have regular medical check-ups.

### 7.2. Storage

#### Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.  
Store products only unopened, in original packing.

#### Special storage conditions:

See point 10.2  
Protect against moisture and store closed.

## 8. Exposure controls/personal protection

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the OES, MEL or MAK values, suitable breathing protection should be worn.  
Only applies when exposure limits are listed in this section.

Chemical name	content %	OES, MEL, MAK, TRK	BMGV, BAT
Oil mist, mineral		5 mg/m <sup>3</sup>	
8.1 Respiratory protection: Filter A - P2 (EN 141)		If OES-, MEL- or MAK-value is exceeded.	
8.2 Hand protection: Protective hand cream recommended.		Protective nitrile gloves (EN 374)	
8.3 Eye protection:		Tight fitting protective goggles (EN 166) with side protection, with danger of projections.	
8.4 Skin protection:		Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)	
Additional information on hand protection - No tests have been performed. Selection made for preparations according to the best available knowledge and information on the ingredients. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer. In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.			

## 9. Physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
10 % pH-value:	k.D.v.
Boiling point / range (°C):	k.D.v.
Melting point / range (°C):	- 50
Flash point (°C):	240
Autoflammability:	k.D.v.
Minimum limit of explosion:	k.D.v.
Maximum limit of explosion:	k.D.v.
Vapour pressure:	k.D.v.
Relative density (g/ml):	0,860
Solubility in water:	Insoluble
Viscosity:	78 mm <sup>2</sup> /s/40°C , 13,9 mm <sup>2</sup> /s/100°C

## 10. Stability and reactivity

### 10.1 Conditions to avoid

See point 7  
 Stable when handled and stored correctly.  
 Protect from humidity.  
 Open flame, ignition sources

### 10.2 Materials to avoid

See point 7  
 Avoid contact with strong oxidizing agents.  
 Avoid contact with other chemicals.

### 10.3 Hazardous decomposition products

See point 5.3

## 11. Toxicological information

### 11.1 Acute toxicity and immediate effects

11.1.1 Ingestion, LD50 rat oral (mg/kg):	k.D.v.
11.1.2 Inhalation, LC50 rat inhal.(mg/l/4h):	k.D.v.
11.1.3 Skin contact, LD50 rat dermal (mg/kg):	k.D.v.
11.1.4 Eye contact:	k.D.v.

### 11.2 Delayed and chronic effects

11.2.1 Sensitization:	k.D.v.
11.2.2 Carcinogenicity:	k.D.v.
11.2.3 Mutagenicity:	k.D.v.

4 / 5 EN

Revision: 17.07.2003 Replaces the version of: 17.07.2003 Printing date: 05.02.2004  
VOLLSYNT.ENERGY MOT.OIL0W40 5L  
Art.:2050

11.2.4 Reproductive toxicity: k.D.v.  
11.2.5 Narcosis: k.D.v.

### 11.3. Further information

No classification according to calculation procedure.  
The following may occur:  
Drying of the skin.  
Irritation of the skin.  
May cause sensitization by skin contact.

## 12. Ecological information

Water hazard class: 2  
Self classification: Yes (VwVwS)  
Persistence and degradability:  
Not readily biodegradable \*  
Behaviour in sewage plants: Mechanical precipitation possible.  
Aquatic toxicity: See point 3.  
Ecological toxicity: k.D.v.  
\* Zinc alkyl dithiophosphate

## 13. Disposal considerations

### 13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

07 06 99 - wastes not otherwise specified

13 02 05 - mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

### 13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

## 14. Transport information

### General statements

UN-Number: n.a.

### Road/Rail-transport (ADR/RID)

Class/packing-group: n.a.

Classification code: n.a.

LQ: n.a.

### Transport by sea

IMDG-code: n.a. (class/packing-group)

EmS:

Marine Pollutant: n.a.

### Transport by air

IATA: n.a. (class/secondary danger/packing-group)

### Additional information:

Non-dangerous material according to Transport Regulations.

## 15. Regulatory information

**Classification according to Dangerous Product Regulations incl. EC Guidelines  
(67/548/EEC and 1999/45/EC)**

5 / 5 EN

Revision: 17.07.2003 Replaces the version of: 17.07.2003 Printing date: 05.02.2004

VOLLSYNT.ENERGY MOT.OIL0W40 5L

Art.:2050

Symbols: Not applicable

Indications of danger: --

R-phrases:

S-phrases:

Additions:

Contains

Calcium alkylaryl sulfonate

May produce an allergic reaction.

Safety data sheet available for professional user on request.

Observe restrictions: n.a.

## 16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany): 10

Revised points: n.a.

38 Irritating to skin.

41 Risk of serious damage to eyes.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

## Legend:

n.a. = not applicable / n.v., k.D.v. = not available / n.g. = not checked / OES = Occupational exposure standard

MEL = Maximum exposure limit / BMGV = Biological monitoring guidance value / MAK = Maximum concentration for work place (Germany) / TRK = Technical guidance concentration (Germany) / BAT = Biological tolerance for work place (Germany)

VbF = Regulations for flammable liquids (Germany) / TRbF = Technical regulations for flammable liquids (Germany)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC-CH=Volatile organic compounds(VOCV - Switzerland)/AOX=Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: 01805-CHEMICAL / 01805-243 642, Fax: 05233-941790**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.