

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

MAXLIFE™ ATF

Valvoline MaxLife™ ATF (Automatic Transmission Fluid) is the first fluid of its kind that is specifically formulated for higher mileage automatic transmissions. It is formulated with premium base stocks, unique seal conditioners, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers, among other performance packages. Valvoline MaxLife™ is recommended for use in high-mileage, new and rebuilt transmissions and will not void new car warranties.

The Valvoline MaxLife™ ATF Advantages:

- Condition transmission seals to prevent leaks
- Reduce varnish formation and wear
- Improve and maintain smooth shifting longer than conventional automatic transmission fluids
- Provide excellent flow properties at low temperatures and greater film protection at high temperatures
- Maximize the life of higher mileage transmissions

Approvals/Performance Levels

Exceeds the latest performance requirements of DEXRON®-III H and MERCON® fluids

Recommended for use in GM, Ford, Mazda, Toyota, Hyundai and others where DEXRON®-III and MERCON® fluids are specified

Suitable for use in Nissan Matic D, Matic J, Matic K applications

Suitable for use in KIA SP-II and SP-III applications and in Mitsubishi Diamond SP-II and SP-III applications

Suitable for use in Toyota/Lexus Type T, T-III and T-IV applications

Suitable for use in Honda/Acura ATF-Z1 (except in CVTs) applications

Test	Typical Property
Viscosity @ 100°C, cSt	7.31
Viscosity @ 40°C, cSt	36.73
Viscosity Index	169
Specific Gravity @ 60°F	0.8518
API Gravity @ 60°F	34.77
Pour Point, °C,	-51
Brookfield Viscosity @ -40°C, cP	16,500
Flash Point, COC, °C	202
ASTM Color	5
Appearance	Red

Effective Date: 8/1/2006

Replaces:

Thom Smith

Doc #-Rev 3